

We UVCare...



PHARMALINE D AF H

Application Optimized UV for Pharmaceuticals

RODEM[®]
SMART SANITARY PROCESSES

www.Rodem.com | (800) 543-7312



UV disinfection for
Purified Water and
distribution
(Hygienic Design-H)


Our PharmaLine D AF H systems are designed for hygiene based on cGMP principles and aimed specifically at providing UV disinfection in Pharmaceutical Purified Water Generation and distribution loop systems where sanitary design is critical. By using a UV system you will disinfect the water, eliminate objectionable organisms, reduce the bio-burden, protect against bio-fouling, lead to fewer CIP / SIP cycles and lower operating costs. Each system comes with a UV intensity sensor to measure the germicidal output of the UV system and make it easy to monitor and log performance. The systems all use low pressure amalgam lamps providing an energy efficient germicidal wavelength and long lamp life to reduce operating costs.

berson


hanovia

aquionics

Potential locations of the PharmaLine D AF H™



KEY FEATURES	WHAT IT GIVES YOU	BENEFITS FOR YOU
INTELLIGENCE		
UV intensity monitor measuring germicidal wavelengths	Continuous verification of performance with low intensity alarm	Easy to monitor and log system performance
OPTIMIZATION		
Single low pressure amalgam lamp technology (LPHO)	Targeted microbiological wavelength	Reduction of microorganisms as part of a multi-barrier purified water process
		Reduced bio-burden in pre-treatment equipment, leading to fewer CIP / SIP cycles and optimised production efficiency
		Protects RO membranes from bio-fouling, reducing CIP frequency and downtime
Designed for the pharmaceutical industry based on cGMP principles	Sanitary design with <math><0.38 \mu\text{m}</math> internal surface finish and tri-clamp connections as standard	Industry compliance; reduced risk of microbiological contamination; enhances control of your process as part of a multi-barrier system
	FDA-approved materials used for all wetted parts	
INTEGRATION		
Compact design	Can be fitted to skids	Easy integration
	Can be retrofitted to existing process	



PharmaLine D AF H (low pressure amalgam lamp)			Dimensions (Inches)										Approx weight (lb)	
Model Number	Maximum Power (W)	UVT (%)	A	B	C	D	E	DN***	K*	L	M**	Chamber (Empty)	Control Cabinet	
PharmaLine D AF H 0003	115	60	36.2	33.1	3	31.5	2.5	1	6.7	11.8	19.3	11	24	
PharmaLine D AF H 0005	115	60	54.6	50.1	3.2	51.2	4	1.5	6.7	11.8	19.3	20	24	
PharmaLine D AF H 0008	165	60	54.6	50.1	3.2	51.2	4	2	6.7	11.8	19.3	20	24	
PharmaLine D AF H 0016	345	60	54.6	50.1	3.2	51.2	4	2	6.7	11.8	19.3	20	24	
PharmaLine D AF H 0030	345	60	56.6	51.2	5.9	51.2	6.6	3	6.7	11.8	19.3	53	24	
PharmaLine D AF H 0090	700	60	78	71.9	7.9	74.8	8.1	6	8.9	15.7	27.2	101	49	

* Allow dimension L in front of cabinet for door opening and panel access.

** M dimension includes the space for the cabinet mounting brackets but you need to allow space below the cabinet for cable entry and access (minimum of 9.8").

*** DN tri-clamp sizes over 3" may not fit with standard sanitary tube. Please consult with Aquionics for correct dimensions.

All dimensions are approximate for clearance purposes only. We have a policy of continuous product development, exact drawings are available on request.

All specifications are subject to change without notification. Your distributor or our account manager can advise on correct sizing and specification requirements.

UV CHAMBER	
Material:	StSt 316L / 1.4404
Internal finish:	<0.38 µm Ra, welds left as laid, electropolished and passivated
External finish:	Sateen polish (120 grit) electropolished and passivated
Process (mating) connections:	Tri-clamp. For sizes see Tri-clamp technical bulletin 910425-0001
Drain connection:	Tri-clamp to ISO 2852
End plate:	Removable tri-clamp
Degree of protection:	IP65 equivalent to NEMA 4 but not for outside use
UV lamp:	Low pressure amalgam
Quartz sleeve	Pure quartz (F200)
Number of UV lamps:	1
Expected lamp life:	12000 hours
Temperature sensor:	Snap stat, on D AF H 0090 only
UV intensity sensor:	Wet UV monitor
Working fluid temperature:	41°F to 104°F
Maximum CIP temperature:	266°F (D AF H 0003 – D AF H 0016) 203°F (D AF H 0030 –D AF H 0090) with cabinet electrically isolated
Hydrostatically pressure tested:	Yes
Chamber mounting:	Horizontal or vertical except D AF H 0090 which is horizontal only
Operating pressure:	10 bar (positive pressure only)
Seals:	EPDM, FDA 21 CFR 177.2600, USP Class VI 250°F approved

OPTIONS	
Document Support Pack	
Cabinet material:	Stainless steel 304
Operation and Maintenance manual and printed Installation and Commissioning manual in Chinese, English, French, German and Spanish	
Maximum CIP temperature: 266°F (D AF H 0030 – D AF H 0090, panel switched off)	
Welder Document Pack for chamber construction	
Skid mounting (not ship board or earthquake zone)	
CABINET (CONTROLLER ELECTRON RCM)	
Material:	Polyester coated carbon steel
Degree of protection:	IP66 / NEMA 4 except D AF H 0090 which is IP54 / NEMA 12
Supply voltages (nominal):	230 V (+/-10%), 50/60 Hz
Operating temperature range:	41°F to 104°F
Relative humidity:	<95% non-condensing except D AF H 0090 which is 85%
Cooling fans:	D AF H 0090 only
Interconnecting cable lengths:	16.4 ft

CUSTOMER OUTPUTS	
4-20 mA passive output:	UV intensity %
VFC outputs:	Lamp ON and Low UV warning
CUSTOMER INPUTS	
VFC inputs:	Remote stop/start and remote reset
CUSTOMER COMMUNICATIONS PORT	
None	

APPROVALS	
CE marked	



PHARMALINE D AF H

Also available in our Pharmaceutical product range...



PHARMALINE PQ+PQH

3rd party validated systems for critical disinfection



PHARMALINE DO

Ozone removal and disinfection



PHARMALINE DC

Chlorine removal



berson



hanovia



aquionics

www.weuvcare.com

BERSON, HANOVIA & AQUIONICS WORKING TOGETHER AS PART OF THE HALMA GROUP.

Netherlands

t: +31 40 2907777
e: sales@bersonuv.com

China

t: +86 21 61679599
e: china@hanovia.com

USA

t: +1 980 256 5700
e: sales@aquionics.com

Germany

t: +49 800 5892779
e: verkauf@hanovia.com

Malaysia

t: +60 16 440 8834
e: asia@hanovia.com

Canada

t: +1 980.256.5700
e: sales@aquionics.com

United Kingdom

t: +44 1753 515300
e: sales@hanovia.com

Mexico

t: +1 980.256.5700
e: sales@aquionics.com



A **Halma** company